

# TECHNICAL DATASHEET

## H05VV-F / 60227 IEC 53 (Cu/PVC/PVC)

### APPLICATION

For household appliances (refrigerators, spin dryers, etc.) under medium mechanical stresses, also in damp and wet spaces.



Number of cores x Nominal cross section	mm <sup>2</sup>	3x1,5
Rated voltage (U <sub>0</sub> /U)	V	300/500
Applicable standards	-	EN 50525-2-11, IEC 60227-5

### 1 CONDUCTOR

Material of conductor	-	Class 5 fine stranded copper
Applicable standard	-	EN 60228, IEC 60228

### 2 INSULATION

Material of insulation	-	PVC (Polyvinyl chloride) acc. to EN 50363-3 TI 2
	-	PVC (Polyvinyl chloride) acc. to IEC 60227-1 PVC/D
Thickness of insulation	mm	0,65
Diameter of insulation	mm	2,80
Identification of cores	HD 308 S2	Brown - Blue - Green/Yellow

### FILLER

Material of filler	-	PVC (Polyvinyl chloride)
Thickness of filler	mm	0,20
Diameter of filler	mm	6,25

### 3 OUTER SHEATH

Material of outer sheath	-	PVC (Polyvinyl chloride) acc. to EN 50363-4-1 TM 2
	-	PVC (Polyvinyl chloride) acc. to IEC 60227-1 PVC/ST5
Thickness of outer sheath	mm	0,80
Overall cable diameter (approx)	mm	7,80
Colour of outer sheath	-	WHITE

### TECHNICAL DATAS AND SPECIFICATIONS

Maximum resistance of the conductor at 20 °C	ohm/km	13,30
Current carrying capacity	A	16
AC Test voltage	V	2000
Minimum bending radius during laying	mm	5xCable Ø
Weight of cable (approx)	kg/km	107
Temperature range	°C	-20 / 70
Maximum operating temperature	°C	70
Maximum short circuit temperature (max. 5 sec.)	°C	160
Flame propagation test on single cable	-	EN 60332-1-2, IEC 60332-1-2



-20 / +70 °C  
Temperature range



70 °C  
Max. operating temperature



160 °C  
Max. short circuit (max. 5 sec.)



Flexible Cable



EN-IEC 60332-1-2  
Flame test standard



RoHS  
Compliance



REACH  
Compliance



European  
Conformity



Eurasian  
Conformity